

# Cipoxy CG

**Cipoxy CG** is a **self levelling, two component epoxy based clear top coat** recommended for performance enhancement of the floor toppings. It has excellent adhesion properties over various types of over lays.

### Properties:

- Excellent adhesion.
- Excellent self leveling properties.
- High gloss.
- Water clear.

### Application areas:

Cipoxy CG is used as topcoat in conjunction with Cipoxy range of floor toppings such as epoxy terrazzo floorings, decorative quartz floorings, epoxy flakes floorings etc.

### Direction to use:

- Ensure that the top coat of CIPOXY SL/SLC is properly cured.
- Cipoxy CG resin is water white clear. Stir it well before mixing with hardener.
- Mix Cipoxy CG resin and Cipoxy CG hardener in 2 : 1 ratio by volume.
- Agitate the mixture for 10 minutes.
- Apply by leveler at the thickness of 500-1000 microns.
- De aerate the layer by using spike roller.
- Allow to cure for overnight.

### Typical physical properties:

Type	Epoxy- cycloaliphatic amine
Mixing ratio(R:H)	2:1 by volume
Appearance	Clear transparent.
Finish	High Gloss.
Flash point	Above 100° C
Pot life	45 - 60 min.
Surface dry	3 - 4 hours
Tack free dry	7 - 8 hours
Hard dry	24 hours
Theoretical Coverage	2 sq.m per litre @ 500 microns
Application method	Leveller & spike roller.
Clean up	PUT 502
Shelf life	12 months.