

FQ Sand

MISCELLANEOUS

Formulated Aggregates

Sr.	Type	Used with
1	FQ Sand 150	Self smoothing screed, along with Cipoxy 14 / 16
2.	FQ Sand 75	Used in sealing coats, for screeds below 1mm. Can be used in top coats too.
3.	FQ Sand 200	Used in conjunction with Cipoxy 15 for thickness between 1500-2000 microns
4.	FQ Sand 250	Used in conjunction with Cipoxy 15 for thickness between 2000 - 2500 microns
5.	FQ Sand 300	Used in conjunction with Cipoxy 15 for thickness between 3000 - 3500 microns
6.	FQ Sand 350	Used in conjunction with Cipoxy 15 for thickness of 3500 microns
7.	FQ Sand 1000	Used in conjunction with Cipothane 30 for high strength screeds

Diluents for PU, Epoxy & EPU coatings

Sr.	Thinner	Used as diluents for
1	PUT 501	PU Adhesives
2.	PUT 502	Cleaning tools, brushes etc
3.	PUT 503	General purpose thinner for PU
4.	PUT 505	Cleaning thinner for plastics
5.	PUT 506	PU wall coatings
6.	PUT 508	Epoxy based paints
7.	PUT 509	P U based paints
8.	PUT 510	NC based paints

Thinners