

# Finish Prime

**Finish Prime** is **water based single component primer**, specially developed as a tie coat between Walputty and PUD based coatings such as Walkote G/M, Walkote E and Walkote 2 K. Finishprime should be applied on the acrylic putties in order to have a good bond with PUD based coatings. It has excellent adhesion to acrylic putties as well as Walkote range of products.

### Properties:

- Excellent adhesion.
- Penetrating properties.
- Water thinnable
- Excellent bond to Acrylic, PUD & PU top coats.

### Application areas:

- Finishprime is used as primer in conjunction with PUD range of wall toppings.

### Direction to use:

- The wall should be matured before wall coating is applied.
- In case the levelling is not proper, it could be done with the usual plaster of Paris treatment or similar cement based putties.
- Now sand the surface with sandpaper No. 100.
- Apply Walputty to cover up surface imperfections.
- Repeat the treatment till a smooth, leveled surface is obtained. Allow to dry over night.
- Sand the surface with suitable grit paper.
- Apply Finish Prime by roller and allow to cure for 3-4 hours.
- Now the surface is ready to receive Walkote or Walkote 2K.

### Typical physical properties:

Type	Waterborne PUD
Non volatile %	50%
Finish	Satin, smooth velvet finish.
Drying time:	
Surface dry	10 - 25 minutes
Tack free dry	1 hour
Hard dry	24 hours
Theoretical Coverage	120 - 125 sq.ft. / ltr. / coat
Application	Roller
Dilution	Water
Clean up	Water
Shelf life	1 year in the unopened container
Packing	1, 5 & 20 lts.