

# Walkote

**Walkote** is a water thinnable, PUD (Polyurethane dispersion) based wall coating recommended for interiors and exteriors.

### Features:

- Walkote imparts a satin smooth film which has excellent durability, adhesion and water resistance.
- Walkote meets the clean room specifications for algae and fungi resistance.
- Available in glossy and matt versions.

### Directions to use:

- The walls should be fully matured before Walkote is applied.
- In case the leveling is not proper, it could be done with the usual plaster of Paris treatment or cement based putties..
- Sand the surface with sand paper No 100.
- Apply Walprime by brush.
- Reapply after 1 hour.
- Apply Walputty by a putty knife to cover up surface dents and imperfections.
- Allow to dry.
- Repeat the operation till you get a smooth and levelled surface.
- Allow to dry for 24 hours.
- Sand the surface
- Apply Finish Prime and allow to dry for 1-2 hours.
- Apply Walkote after diluting with water (10-15%) by roller / brush.
- Allow to dry for 2-3 hours.
- Reapply.

### Typical physical properties

Type	Water borne PU
Non volatile %	60 ± 2
Finish	Semi glossy
Drying time:	
Surface dry	10 - 25 minutes
Tack free dry	1 hour
Hard dry	24 hours
Theoretical Coverage	10-11 sqm/ ltr /coat @ 50 microns.
Application	Roller
Dilution	Water
Clean up	Water
Shelf life	1 year in the unopened container
Packing	1, 5 & 20 lts.