

Waltouch

Waltouch is a **100% acrylic emulsion pigmented coating**, possessing excellent durability, adhesion, gloss and water resistance.

Waltouch, which imparts a satin, smooth velvet finish, is recommended as premium coatings for internal and external walls. .

Features:

- Excellent exterior durability.
- Fast hardness development.
- Superior adhesion and water resistance.
- Excellent dirt pick up resistance.

Directions to use:

- The walls should be matured before Waltouch is applied.
- In case the leveling is not proper, it could be done with the usual plaster of Paris treatment or similar cement based putties..
- Sand the surface with sand paper No. 100.
- Apply Walprime by brush.
- Reapply after 1 hour.
- Apply Walputty by a putty knife to cover up surface dents and imperfections.
- Allow to dry.
- Repeat the operation till you get a smooth surface.
- Allow to dry for 24 hours.
- Sand the surface
- Apply Waltouch after diluting with water (10-15%) by roller / brush.
- Allow to dry for 2-3 hours.
- Reapply.

Typical Physical properties:

Type	100% pure acrylic emulsion
Non volatile %	55%
Finish	Satin, smooth velvet finish.
Drying time:	
Surface dry	10 - 25 minutes
Tack free dry	1 hour
Hard dry	24 hours
Theoretical Coverage	120 - 125 sq.ft. / lt. / coat
Application	Roller
Dilution	Water
Clean up	Water
Shelf life	1 year in the unopened container